

### Description

The TLP281-4x series combine an AlGaAs infrared emitting diode as the emitter which is optically coupled to a silicon planar phototransistor detector in a plastic SO16 package with different lead forming options. With the robust coplanar double mold structure, TLP281-4x series provide the most stable isolation feature.


### Features

- High isolation 3750 VRMS
- CTR flexibility available see order information
- DC input with transistor output
- Operating temperature range - 55 °C to 110 °C
- REACH compliance
- Halogen free
- MSL class 1

### Applications

- Switch mode power supplies
- Programmable controllers
- Household appliances
- Office equipment


**SCHEMATIC**



**PIN DEFINITION**

|                     |                  |
|---------------------|------------------|
| <b>1,3,5,7 :</b>    | <b>Anode</b>     |
| <b>2,4,6,8 :</b>    | <b>Cathode</b>   |
| <b>9,11,13,15:</b>  | <b>Emitter</b>   |
| <b>10,12,14,16:</b> | <b>Collector</b> |

**PACKAGE OUTLINE**



| ABSOLUTE MAXIMUM RATINGS    |           |         |                  |      |
|-----------------------------|-----------|---------|------------------|------|
| PARAMETER                   | SYMBOL    | VALUE   | UNIT             | NOTE |
| INPUT                       |           |         |                  |      |
| Forward Current             | $I_F$     | 60      | mA               |      |
| Peak Forward Current        | $I_{FP}$  | 1       | A                | 1    |
| Reverse Voltage             | $V_R$     | 6       | V                |      |
| Input Power Dissipation     | $P_i$     | 100     | mW               |      |
| OUTPUT                      |           |         |                  |      |
| Collector - Emitter Voltage | $V_{CEO}$ | 80      | V                |      |
| Emitter - Collector Voltage | $V_{ECO}$ | 7       | V                |      |
| Collector Current           | $I_C$     | 50      | mA               |      |
| Output Power Dissipation    | $P_o$     | 150     | mW               |      |
| COMMON                      |           |         |                  |      |
| Total Power Dissipation     | $P_{tot}$ | 200     | mW               |      |
| Isolation Voltage           | $V_{iso}$ | 3750    | V <sub>rms</sub> | 2    |
| Operating Temperature       | $T_{opr}$ | -55~110 | °C               |      |
| Storage Temperature         | $T_{stg}$ | -55~125 | °C               |      |
| Soldering Temperature       | $T_{sol}$ | 260     | °C               |      |

Note 1. 100µs pulse, 100Hz frequency

Note 2. AC For 1 Minute, R.H. = 40 ~ 60%


| <b>ELECTRICAL OPTICAL CHARACTERISTICS at Ta=25°C</b> |                      |                  |                  |      |      |                                |                |
|--|----------------------|------------------|------------------|------|------|--------------------------------|----------------|
| PARAMETER  | SYMBOL               | MIN              | TYP.             | MAX. | UNIT | TEST CONDITION                 | NOTE           |
| <b>INPUT</b>   |                      |                  |                  |      |      |                                |                |
| Forward Voltage                                      | V <sub>F</sub>       | -                | -                | 1.4  | V    | IF=10mA                        |                |
| Reverse Current                                      | I <sub>R</sub>       | -                | -                | 10   | μA   | VR=6V                          |                |
| Input Capacitance                                    | C <sub>in</sub>      | -                | 10               | -    | pF   | V=0, f=1kHz                    |                |
| <b>OUTPUT</b>  |                      |                  |                  |      |      |                                |                |
| Collector Dark Current                               | I <sub>CEO</sub>     | -                | -                | 100  | nA   | VCE=20V, IF=0                  |                |
| Collector-Emitter Breakdown Voltage                  | BV <sub>CEO</sub>    | 80               | -                | -    | V    | IC=0.1mA, IF=0                 |                |
| Emitter-Collector Breakdown Voltage                  | BV <sub>ECO</sub>    | 7                | -                | -    | V    | IE=0.1mA, IF=0                 |                |
| <b>TRANSFER CHARACTERISTICS</b>                      |                      |                  |                  |      |      |                                |                |
| Current Transfer Ratio                               | TLP281-4GB           | CTR              | 100              | -    | 600  | %                              | IF=5mA, VCE=5V |
|  | TLP281-4             |                  | 50               | -    | 600  |                                |                |
|  |                      |                  |                  |      |      |                                |                |
|  |                      |                  |                  |      |      |                                |                |
|  |                      |                  |                  |      |      |                                |                |
| Collector-Emitter Saturation Voltage                 | V <sub>CE(sat)</sub> | -                | 0.1              | 0.2  | V    | IF=10mA, IC=1mA                |                |
| Isolation Resistance                                 | R <sub>ISO</sub>     | 10 <sup>12</sup> | 10 <sup>14</sup> | -    | Ω    | DC500V, 40 ~ 60% R.H.          |                |
| Floating Capacitance                                 | C <sub>IO</sub>      | -                | 0.4              | 1    | pF   | V=0, f=1MHz                    |                |
| Response Time (Rise)                                 | t <sub>r</sub>       | -                | 3                | 18   | μs   | VCE=2V, IC=2mA<br>RL=100Ω      | 3              |
| Response Time (Fall)                                 | t <sub>f</sub>       | -                | 4                | 18   | μs   |                                | 3              |
| Cut-off Frequency                                    | f <sub>c</sub>       | -                | 80               | -    | kHz  | VCE=2V, IC=2mA<br>RL=100Ω,-3dB | 4              |

Note 3. Fig.12&13


Note 4. Fig.14

**CHARACTERISTIC CURVES**


**Fig.1 Forward Current vs. Ambient Temperature**




**Fig.2 Collector Power Dissipation vs. Ambient Temperature**




**Fig.3 Forward Current vs. Forward Voltage**




**Fig.4 Collector Dark Current vs. Ambient Temperature**



**Fig.5 Collector Current vs. Collector-emitter Voltage**




**Fig.6 Collector Current vs. Collector-emitter Voltage**




**CHARACTERISTIC CURVES**


**Fig.7 Normalized Current Transfer Ratio vs. Forward Current**




**Fig.8 Normalized Current Transfer Ratio vs. Ambient Temperature**




**Fig.9 Collector-emitter Saturation Voltage vs. Ambient Temperature**



**Fig.10 Switching Time vs. Load Resistance**




**Fig.11 Frequency Response**




**TEST CIRCUITS**


**Fig.12 Test Circuits of Response Time**




**Fig.13 Curves of Response Time**




**Fig.14 Test Circuits of Frequency Response**



**PACKAGE DIMENSIONS (Dimensions in mm unless otherwise stated)**




**Recommended Solder Mask (Dimensions in mm unless otherwise stated)**



**CARRIER TAPE SPECIFICATIONS (Dimensions in mm unless otherwise stated)**

**Option T1**



| Description                               | Symbol | Dimension<br>mm (inch) |
|---|--------|------------------------|
| Tape Width                                | W      | 16 ± 0.3 (0.63)        |
| Pitch of Sprocket Holes                   | P0     | 4 ± 0.1 (0.15)         |
| Distance of Compartment to Sprocket Holes | F      | 7.5 ± 0.1 (0.295)      |
|   | P2     | 2 ± 0.1 (0.079)        |
| Distance of Compartment to Compartment    | P1     | 12 ± 0.1 (0.47)        |



**ORDERING AND MARKING INFORMATION**

**MARKING INFORMATION**



**TLP281-4x: Part Number**  
**I: ISOCOM LIMITED**  
**Y: denotes 2 digit Year code**  
**WW: denotes 2 digit Week code**

**ORDERING INFORMATION**

**TLP281-4x**


TLP – Company Abbr.  
 281-4 – Part Number  
 X – CTR Rank (GB/None)

**PACKING QUANTITY**

| Option | Quantity        | Quantity – Inner box | Quantity – Outer box              |
|--------|-----------------|----------------------|-----------------------------------|
| T1     | 2000 Units/Reel | 1 Reels/Inner box    | 5 Inner box/Outer box = 10k Units |
|        |                 |                      |                                   |

**REFLOW INFORMATION**


**REFLOW PROFILE**



| Profile Feature                 | Sn-Pb Assembly Profile | Pb-Free Assembly Profile |
|---------------------------------|------------------------|--------------------------|
| Temperature Min. (Tsmin)        | 100                    | 150°C                    |
| Temperature Max. (Tsmax)        | 150                    | 200°C                    |
| Time (ts) from (Tsmin to Tsmax) | 60-120 seconds         | 60-120 seconds           |
| Ramp-up Rate (tL to tP)         | 3°C/second max.        | 3°C/second max.          |
| Liquidous Temperature (TL)      | 183°C                  | 217°C                    |
| Time (tL) Maintained Above (TL) | 60 – 150 seconds       | 60 – 150 seconds         |
| Peak Body Package Temperature   | 235°C +0°C / -5°C      | 260°C +0°C / -5°C        |
| Time (tP) within 5°C of 260°C   | 20 seconds             | 30 seconds               |
| Ramp-down Rate (TP to TL)       | 6°C/second max         | 6°C/second max           |
| Time 25°C to Peak Temperature   | 6 minutes max.         | 8 minutes max.           |

**TEMPERATURE PROFILE OF SOLDERING**

**WAVE SOLDERING (JESD22-A111 COMPLIANT)**



**HAND SOLDERING BY SOLDERING IRON**

|                       |            |
|-----------------------|------------|
| Soldering Temperature | 380+0/-5°C |
| Soldering Time        | 3 sec max. |

- One time soldering is recommended for all soldering method.
- Do not solder more than three times for IR reflow soldering.

## DISCLAIMER

- ISOCOM LIMITED is continually improving the quality, reliability, function and design. ISOCOM LIMITED reserves the right to make changes without further notices.
- The characteristic curves shown in this datasheet are representing typical performance which are not guaranteed.
- ISOCOM LIMITED makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, ISOCOM LIMITED disclaims (a) any and all liability arising out of the application or use of any product, (b) any and all liability, including without limitation special, consequential or incidental damages, and (c) any and all implied warranties, including warranties of fitness for particular
- The products shown in this publication are designed for the general use in electronic applications such as office automation, equipment, communications devices, audio/visual equipment, electrical application and instrumentation purpose, non-infringement and merchantability.
- This product is not intended to be used for military, aircraft, automotive, medical, life sustaining or lifesaving applications or any other application which can result in human injury or death.
- Please contact ISOCOM LIMITED sales agent for special application request.
- Immerge unit's body in solder paste is not recommended.
- Parameters provided in datasheets may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated in each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify ISOCOM LIMITED's terms and conditions of purchase, including but not limited to the warranty expressed therein.
- Discoloration might be occurred on the package surface after soldering, reflow or long-time use. It neither impacts the performance nor reliability.